

RESOURCES

JUMP TO 

Fleck 2510 Electromechanical Softener Time Clock



3/4" Control valve fiber-reinforced polymer valve body for superior strength and durability, non-corrosive, and UV-resistant.

Simple to adjust and easy to service with quick access to all internal components
Electromechanical 7- or 12-day time clock, meter delayed, or meter immediate regeneration
Electromechanical timer auxiliary switch
Fiber-reinforced polymer or stainless steel bypass valve

Find out where to purchase online or in a retail location near you.

WHERE TO BUY

RESOURCES

 [PENTAIR FLECK 2510 SERVICE MANUAL](#)



[FLECK 2510 MANUAL \(SPANISH\)](#)[FLECK 2510 MANUAL \(FRENCH CANADIAN\)](#)[PENTAIR LIMITED WARRANTY
RESOURCES](#)[JUMP TO](#) 

SPECIFICATIONS

CONTINUOUS FLOW RATE @ 15 PSI DROP: 19 gpm

MAX. BACKWASH FLOW @ 25 PSI DROP: 17 gpm

INLET OUTLET CONNECTION TYPE - VALVES: NPT, BSP, SWEAT

INLET OUTLET SIZE - VALVES: 3/4", 1", 1-1/4"

VALVE APPLICATION: Filter, Water Softener

Item #:

251001-002

Description:

Time Clock, 12 day, Downflow Softener, 120V/60Hz, U.S. Power Cord, Hardwater Bypass, 1650 Brine Valve, #1 injector, 0.50 GPM BLFC, Environmental Backplate

Item #:

251001-006

Description:

Time Clock, 12 day, Downflow Softener, 120V/60Hz, U.S. Power Cord, Hardwater Bypass, 1650 Brine Valve, #1 injector, 0.50 GPM BLFC, Designer Backplate

Item #:

251001-007

Description:

Time Clock, 12 day, Downflow Softener, 120V/60Hz, U.S. Power Cord, Hardwater Bypass, 1600 Brine Valve, #1 injector, 0.50 GPM BLFC, Environmental Backplate

Item #:

251001-010

Description:

Time Clock, 12 day, Downflow Softener, 120V/60Hz, U.S. Power Cord, Hardwater Bypass, 1650 Brine Valve, #2 injector, 0.50 GPM BLFC, Environmental Backplate

Item #:

251001-011

Description:

Time Clock, 12 day, Downflow Softener, 120V/60Hz, U.S. Power Cord, Hardwater Bypass, 1650 Brine Valve, #2 injector, Blank BLFC, Environmental Backplate

